



# SEAL® 62 Base Laminator



**The SEAL® 62 Base laminator represents SEAL's latest offering to the rapidly growing digital display market. Ideal for mounting and laminating pressure-sensitive graphics up to 61", this machine represents a flexible package at an affordable price - without compromising its functionality.**

The SEAL 62 Base is a pressure-sensitive machine with heat assist on the top roller that ensures superb results with a wide range of materials. Whatever the experience level of the operator, the SEAL 62 Base is easy-to-use, and will deliver genuine flexibility and high performance levels for the small to medium sized user.

Having great capability delivered at an

affordable price, the 62 Base is ideal for sign-makers. It provides the means for these users to finish their images and create more applications, which equals generating greater profitability. This laminator is also suitable for small to medium display based businesses who want to expand their range of applications. With the lower unwind/take-up option, you can encapsulate with pressure-sensitive films.

The SEAL 62 Base is ideal for producing a wide variety of display graphics

Rigid Indoor Displays



Rigid Outdoor Displays



Backlit Displays




Pop-Up Displays



Roll-Up Displays



Floor Graphics



The SEAL 62 Base provides the following features:

#### Optimum performance

- 61" working width to handle a wide range of media
- Adjustable pressure and speed settings for maximum versatility
- 2" nip opening to cover a wide range of substrates
- 2" nip opening suitable for working with a sled for road signs
- Heat assisted top roller for superb lamination performance
- Maximum operating speed of 16.4'/minute
- Manual nip adjustment for precise operation
- Robust, free standing unibody design

#### Ease of use

- Ergonomic control panel for ease of use
- Auto-grip shafts for user friendly webbing
- Swing-up feed table to facilitate easy set up
- Optional roll trough and image guide and leveling feet
- Optional rear power take up

#### Safety

- Foot switch for hands free operation
- Self checking safety eyes for increased operator safety
- ETL Certified (US & Canada) and CE Certified (Europe)

# SEAL® 62 Base

## Technical Specifications

Maximum Working Width	61" (1600 mm)
Maximum Speed	16.4' /min. (5 m/min.)
Maximum Substrate Thickness	2" (50 mm)
Maximum Roller Temperature	104°F (40°C)
Roller Heating	Heat assisted top roller
Maximum Roll Weight	
Unwind	85 lbs (38.5 kg)
Take Up	35 lbs (15.9 kg)
Maximum Roll Diameter	
Top	11.4"
Bottom	11"
Dimensions	
Width	82" (2090 mm)
Height	52" (1326 mm)
Depth (excl. table)	19" (483 mm)
Depth (incl. table)	23" (590 mm)
Working Height	35.5" (900 mm)
Net Weight	530lbs. (240 kg)
Shipping Dimensions	
Width	86" (2184 mm)
Height	61" (1500 mm)
Depth	30" (762 mm)
Shipping Weight	661 lbs. (300 kg)
Electrical Requirements	115 VAC 50/60 Hz, 15A NEMA 5-20 plug
SEAL 62 Base Part Number	
115 VAC	64338A
230 VAC Europe	64339A
SEAL 62 Base Part Number with Factory Installed Roll Trough, Image Guide and Leveling Feet	
115 VAC	62629
Optional Equipment Part Numbers	
Roll Trough	64614A
Leveling Feet (Set of 4)	5406A
Image Guide	64625A
Rear Power Take Up	64623
Lower Take-Up with Autogrip Shaft	64618

Ergonomic control panel for ease of use.



Auto-grip shafts for user friendly webbing.



Optional flip up roll trough for easy feed in



Roll-to-roll option available



ACCO Brands  
Four Corporate Drive  
Lake Zurich, IL 60047-8997  
In USA call 800-222-6462  
www.acco.com

SEAL	SEAL Canada
Four Corporate Drive	7381 Bramalea Road
Lake Zurich, IL 60047	Mississauga Ontario L5S 1C4
U.S.A.	Canada
Tel: 800-257-7325	Tel: 800-257-7325
Fax: 800-966-4554	Fax: 800-966-4554



Contact your local distributor: